



Technical information – v.3.0.2021

# SOLV GEL

## GEL BASED PAINT/GRAFFITI/GLUE AND EPOXY REMOVER

Description :	<div> <div>Benefits:</div> <div> Gel/viscous formulation  Dissolves general paint and glue  Internal &amp; external  Effective on rough surfaces  Easy to use </div> </div> <div> <div>Where to apply:</div> <div> Textured marbles, granites, natural stone and pavers  Terracotta  Agglomerates  Concrete </div> </div> <p>SOLV GEL is a mixture of solvents in a gel emulsion for the removal of spray paint, graffiti, old natural and synthetic glues, adhesives and epoxies from all stone surfaces and facades. Product dissolves quickly graffiti, paint, old ink and felt pen residues, acrylics and clear coatings leaving surface clean and without changing natural appearance of material. The gel formulation allows product to be applied easier to vertical surfaces avoiding drips especially on horizontal surfaces where more contact time is required.</p>
How to use :	<p>Always test first before proceeding with complete product application so to determine product compatibility and final result on material. Protect and cover all surroundings and metallic fixings using PVC sheeting and tape. Wear suitable PPE equipment during product use (gloves, eye protection and clothing). Do not apply where temperatures are below 10°C.</p> <p>Cladding and monuments (Graffiti, paint, ink):</p> <ol style="list-style-type: none"> <li>Cover up all metallic surroundings and surfaces before use. Apply sheeting for eventual product excess or drips.</li> <li>Proceed to apply a thick solution using a soft large bristle brush direct to a pre wetted area to be cleaned.</li> <li>Allow for a surface contact time of 10-20 min before agitating area using white felt pad or bristled brush.</li> <li>Remove all residues using low/high pressured water.</li> <li>On stubborn residues, multiple applications or longer dwelling time may need to be applied.</li> </ol> <p>Floors (Glue and residues):</p> <ol style="list-style-type: none"> <li>Apply directly to residue and allow a contact time of 20-30 minutes.</li> <li>Check regularly the softening of residues or allow in contact until cured residue is lifted or dissolved.</li> <li>Remove residues using a stiff bristled brush or nylon pad. (no to use steel wool pads)</li> <li>Once removed, scrub surface using a alkaline based detergent and remove all residues with clean water.</li> </ol>
Dilutions :	<div> <div>Flooring : -</div> <div>Cladding : Ready to use</div> <div>Scrubbers : -</div> </div>
Safety and technical data:	<p>Before using this product, please read completely product label, TDS and SDS, available from your local dealer or contacting GCHEM. Keep package closed and stored in a cool place. Keep out of the reach of children. Always supply adequate ventilation when using product indoors and do not eat or drink during product use.</p> <div> <div>Appearance: Gel</div> <div>Odour: Characteristic</div> <div>Colour: Transparent</div> <div>pH: 10,5</div> <div>Flashpoint: n/a</div> </div>
Coverage:	Based on type of material and porosity, 1lt of solution will clean from 5 m2.
Packaging: *ADR regulated	1l. (box 12 pcs)    5l. (box 4 pcs)    10l. on request*    25l. on request. *

Our technical advice, whether verbal or in writing is given in good faith without warranty and should not be considered binding towards third parties. We highly suggest that product is used always under the best professional working conditions possible. Product use and application is under the sole responsibility of the user and beyond our control. We guarantee product quality as of our production standards and supplied terms and conditions. Should, in spite of this, liability be established for any damage, it will be limited to the value of the goods delivered by us and used by you.



Mobile: +968 7992 9900

Email: [info@adtoman.com](mailto:info@adtoman.com)

Atheer Diyan Trading

P.O. Box: 888, Postal Code: 322, Ghala Industrial Area, Sultanate of Oman