



# NEUTRO

SOLVENT BASED , ANTI STAIN FOR  
TEXTURED MARBLES, GRANITES AND  
NATURAL STONES

<b>Description:</b>	<table><tr><td><b>Benefits:</b></td><td><b>Where to apply:</b></td></tr><tr><td>Oil/Water repellent</td><td>Textured, rough marbles, granites, natural stone.</td></tr><tr><td>Breathable</td><td>Internal &amp; external use</td></tr><tr><td>Penetrating</td><td>Agglomerates</td></tr><tr><td>Non shine or sheen</td><td>Travertines, slates and limestones</td></tr><tr><td>No color change</td><td></td></tr></table> <p>NEUTRO is a solvent based, multi surface oil/water repellent impregnator which will protect all internal or external natural stone from general surface staining, moisture, dirt and grime and water absorption. Treatment can be used on multi surfaces such as; travertine, limestone, slate, terrazzo, Victorian tiles, brick, lava stone and other masonry surfaces. Product provides a natural look finish. Protected surfaces will maintain their natural finish, are breathable and are non -yellowing. UV resistant.</p>	<b>Benefits:</b>	<b>Where to apply:</b>	Oil/Water repellent	Textured, rough marbles, granites, natural stone.	Breathable	Internal & external use	Penetrating	Agglomerates	Non shine or sheen	Travertines, slates and limestones	No color change	
<b>Benefits:</b>	<b>Where to apply:</b>												
Oil/Water repellent	Textured, rough marbles, granites, natural stone.												
Breathable	Internal & external use												
Penetrating	Agglomerates												
Non shine or sheen	Travertines, slates and limestones												
No color change													
<b>How to use:</b>	<p>Always test first before proceeding with complete product application so to determine product compatibility and final result on material. Protect and cover all surroundings and metallic fixings using PVC sheeting and tape. Wear suitable PPE equipment during product use (gloves, eye protection and clothing). Product is ready for use. Do not apply where temperatures are below 10°C</p> <p><b>Existing surfaces:</b> Before protecting old or existing surfaces with NEUTRO, proceed to clean and remove all dirt and grime or any previous treatments and waxes from surface using our products REMOVER or SOLV (strippers) or DETERMAC (alkaline based deep cleaner).</p> <p><b>New installations:</b></p> <ol style="list-style-type: none"><li>1. Always apply to dry and clean surfaces.</li><li>2. Apply one or two coats (depending on porosity of stone) of NEUTRO uniformly by low pressure spray, cloth or brush to surface to be treated. Allow a contact time of 5/10 minutes so to allow complete penetration into material before removing any excess product using a clean cotton cloth.</li><li>3. Allow a complete curing time of surface for 24 hours for complete surface protection.</li></ol>												
<b>Maintenance:</b>	<p>NEU TRO is compatible with all ph ne utral deter gents. Please refer to the below products for cleaning of treated surface. (please refer to product TDS for full product use and instructions:</p> <table><tr><td><b>Floors:</b></td><td><b>Daily:</b> DETERCLEANER</td><td><b>Periodic:</b> DETERMAC</td></tr><tr><td></td><td><b>Sanitizer:</b> DETERSAN</td><td></td></tr><tr><td><b>Worktops and surfaces:</b></td><td><b>Daily:</b> DETERSAN</td><td><b>Periodic:</b> - trigger</td></tr></table>	<b>Floors:</b>	<b>Daily:</b> DETERCLEANER	<b>Periodic:</b> DETERMAC		<b>Sanitizer:</b> DETERSAN		<b>Worktops and surfaces:</b>	<b>Daily:</b> DETERSAN	<b>Periodic:</b> - trigger			
<b>Floors:</b>	<b>Daily:</b> DETERCLEANER	<b>Periodic:</b> DETERMAC											
	<b>Sanitizer:</b> DETERSAN												
<b>Worktops and surfaces:</b>	<b>Daily:</b> DETERSAN	<b>Periodic:</b> - trigger											
<b>Safety and technical data:</b>	<p>Before using this product, please read completely product label, TDS and SDS , available from your local dealer or contacting GCHEM. Keep package closed and stored in a cool place. Keep out of the reach of children. Always supply adequate ventilation when using product indoors and do not eat or drink during product use. Shelf life: 2-3 years with cap completely closed.</p> <table><tr><td><b>Appearance:</b> Limpid</td><td><b>Odour:</b> Mild Solvent</td><td><b>Specific Density (20°C):</b> 0,850 gr/cm<sup>3</sup></td></tr><tr><td><b>Colour:</b> Transparent</td><td><b>pH:</b> n/a</td><td><b>Flashpoint:</b> ≥ 15 °C</td></tr></table>	<b>Appearance:</b> Limpid	<b>Odour:</b> Mild Solvent	<b>Specific Density (20°C):</b> 0,850 gr/cm <sup>3</sup>	<b>Colour:</b> Transparent	<b>pH:</b> n/a	<b>Flashpoint:</b> ≥ 15 °C						
<b>Appearance:</b> Limpid	<b>Odour:</b> Mild Solvent	<b>Specific Density (20°C):</b> 0,850 gr/cm <sup>3</sup>											
<b>Colour:</b> Transparent	<b>pH:</b> n/a	<b>Flashpoint:</b> ≥ 15 °C											
<b>Coverage:</b>	Based on type of material and porosity, 1lt of product will cover from 4 m2 up to 20 m2. (Marbles, granites & travertines 10-12m2), (Sandstones, limestones 4-8m2), (Terrazzo 15-20m2), (Slate 8-10m2)												
<b>Packaging:</b> *ADR regulated	1l. (box 10 pcs) 5l. (box 2 pcs) 10l. on request* 25l. on request. *												

Our technical advice, whether verbal or in writing is given in good faith without warranty and should not be considered binding towards third parties. We highly suggest that product is used always under the best professional working conditions possible. Product use and application is under the sole responsibility of the user and beyond our control. We guarantee product quality as of our production standards and supplied terms and conditions. Should, in spite of this, liability be established for any damage, it will be limited to the value of the goods delivered by us and used by you.