

## **NO RISALITA**

## ACRYLIC BASED, UNDERSIDE TREATMENT AGAINST RISING MOSIT URE AND STAINING.

Description:

Where to apply: Benefits:

Water based Terrazzo, Sandstones, natural

Breathable stone.

Prevents salts Internal & external use Prevents water marks Marbles, limestones, granites

Low odour

NO RISALITA is a water based, protective treatment specific for the application to the back side of floor or wall tiles and materials. Product avoid potential staining and marking caused by eventual rising humidity and moisture contained inside cement bedding or adhesive mixture.

Treatment is highly recommended for all materials that suffer problems and marking due to underfloor humidity and moisture. Product will block the appearance of oxidation, staining, pitting and water marks or eventual salts and efflorescence from forming on surface. Product can be applied to the back side or to sides of tile in contact with cement based adhesive and will not affect bonding and adhesion.

NO RISALITA is colorless and is applicable to all stone surfaces. Highly recommended on white marbles and in cases where a low quality adhesive or a simple cement/sand/mortar mix is used for fixing.

How to use:

Always test first before proceeding with complete product application so to determine product compatibility and final result on material. Protect and cover all surroundings and metallic fixings using PVC sheeting and tape. Wear suitable PPE equipment during product use (gloves, eye protection and clothing). Do not apply where temperatures are below 10°C.

Best applied during a dry lay process.

- During a dry lay process, apply NO RISALITA by using a roller, large bristle brush or spray uniformly to the underside and sides of tile or
- 2. Allow a curing time of 6 hours before proceeding with installation.
- 3. On compact surfaces, product can be used diluted following a ratio of 1:9 with water.

Maintenance:

Coverage:

NO RISALITA does not require any future maintenance.

Floors: Daily: -Periodic: -Sanitizer: -

Daily: -Worktops and surfaces: Periodic: -

Safety and technical dat a:

Before using this product, please read completely product label, TDS and SDS, available from your local dealer or contacting GCHEM. Keep package closed and stored in a cool place. Keep out of the reach of children. Always supply adequate ventilation when using product indoors and do not eat or drink during product use. Shelf life: 1-2 years.

Appearance: Limpid Odour: inodore Specific Density  $(20^{\circ}C): 1,010 \text{ gr/cm}^3$ 

Colour: Milky pH: n/a Flashpoint: y, 1lt of product will cover from 8

Based on type of material and porosit to 20 m2. (compact materials)

1l. (box 10 pcs) 5l. (box 2 pcs) 10l. on request \* 25l. on request. \* Packagin q: \*ADR regulated

Our technical advice, whether verbal or in writing is given in good faith without warranty and should not be considered binding towards third parties. We highly suggest that product is used always under the best professional working conditions possible. Product use and application is under the sole responsibility of the user and beyond our control. We quarantee product quality as of our production standards and supplied terms and conditions. Should, in spite of this, liability be established for any damage, it will be limited to the value of the goods delivered by us and used by you.



Mobile: +968 7992 9900 Email: info@adtoman.com

Atheer Divan Trading

P.O. Box: 888, Postal Code: 322, Ghala Industrial Area, Sultanate of Oman