



PROGRES

SOLVENT BASED , LOW ODOUR, ANTI STAIN
FOR POLISHED PORCE LAIN TILES

Description :	<div>Benefits:</div> <div>Oil/Water repellent Breathable Transparent Non yellowing- UV resistant Low odour</div> <div>Where to apply: Polished marbles, granites, natural stone. Internal & external use Agglomerates Porcelain tiles</div> <div>Water/oil protective and anti-stain treatment for all polished and honed porcelain tiles, ceramics, marbles, granites and natural stones used for flooring and on internal furnishing such as table tops, worktops, benches, vanity areas and wet rooms. Product penetrates deep inside material, blocking staining or discoloration caused by humidity and moisture. Product can be applied before or post installation to protect surfaces from staining and marking caused oils & grease, water-based substances, food staining, dirt and grime, yellowing, oxidations and atmospheric conditions. Based on its specific formulation, PROGRES maintains the natural finish and color of material, while allowing vapor transmission. UV resistant, non-yellowing and low odor solution.</div>
How to use :	<div>Always test first before proceeding with complete product application so to determine product compatibility and final result on material. Protect and cover all surroundings and metallic fixings using PVC sheeting and tape. Wear suitable PPE equipment during product use (gloves, eye protection and clothing). Product is ready for use. Do not apply where temperatures are below 10°C</div> <div><div>1. Always apply to dry and clean surfaces.</div><div>2. Apply PROGRES uniformly by low pressure spray, cloth or brush to surface to be treated. Allow contact time of 5/10 minutes so to allow complete penetration into material before removing excess product using a clean cotton cloth.</div><div>3. After 1 hour remove any eventual remaining residues from surface using a felt pad or cotton cloth. (Dry residues or excess can be removed using a fine steel wool pad)</div><div>4. Allow a complete curing time of surface for 72 hours for complete surface protection.</div></div>
Maintenance:	<div>PROGRES is compatible with ph neutral detergents. Please refer to the below products for cleaning of treated surface. (please refer to product TDS for full product use and instructions:</div> <div><div>Floors:</div><div>Daily: DETERCLEANER Sanitizer: DETERSAN</div><div>Periodic: DETERMAC</div></div> <div><div>Worktops and surfaces:</div><div>Daily : DETERSAN trigger</div><div>Periodic: -</div></div>
Safety and technical data:	<div>Before using this product, please read completely product label, TDS and SDS, available from your local dealer or contacting GCHEM. Keep package closed and stored in a cool place. Keep out of the reach of children. Always supply adequate ventilation when using product indoors and do not eat or drink during product use. Shelf life: 1-2 years.</div> <div><div>Appearance: Limpid</div><div>Odour: Mild Solvent</div><div>Specific Density (20°C): 0,820 gr/cm³</div></div> <div><div>Colour: Transparent</div><div>pH: n/a</div><div>Flashpoint: ≥62°C</div></div>
Coverage:	Based on type of material and porosity, 1lt of product will cover from 8 m2 up to 35 m2.
Packaging:	<div>*ADR regulated</div> <div>1l. (box 10 pcs)5l. (box 2 pcs)10l. on request*25l. on request. *</div>

Our technical advice, whether verbal or in writing is given in good faith without warranty and should not be considered binding towards third parties. We highly suggest that product is used always under the best professional working conditions possible. Product use and application is under the sole responsibility of the user and beyond our control. We guarantee product quality as of our production standards and supplied terms and conditions. Should, in spite of this, liability be established for any damage, it will be limited to the value of the goods delivered by us and used by you.