



ZEUS

**SOLVENT BASED, SUPREME HIGH PERFORMANCE,
ANTI STAIN SOLUTION FOR ALL SURFACES – FOOD
CONTACT SAFE**

Description:	<table><tr><td>Benefits:</td><td>Where to apply:</td></tr><tr><td>Oil / Water repellent Breathable, low odour Deeper penetration Non yellowing- UV resistant Long lasting protection</td><td>Polished textured, honed marbles, granites, natural stone. Internal & external use Agglomerates, engineered stone</td></tr></table> <p>ZEUS is supreme protective solution for all stone surfaces (worktops and floors) in marble, granite and natural stone. Products protects material from deep inside creating a barrier against surface staining from oil and water-based substances offering a longer durability and repellency compared to standard sealers. ZEUS is breathable and allows water vapor to escape avoiding surface discoloration, yellowing, oxidations and appearance of surface marks caused by potential humidity and moisture. Product can be applied in both a pre- and post-phase of installation. Product is odorless and UV resistant, will not leave surface film or residues and will maintain the natural colour and finish of material. ZEUS can be applied to all polished and non-polished stone surfaces such as marbles, granites, limestone's, quartzite's, terrazzo, terracotta, cement, agglomerates and much more.</p>	Benefits:	Where to apply:	Oil / Water repellent Breathable, low odour Deeper penetration Non yellowing- UV resistant Long lasting protection	Polished textured, honed marbles, granites, natural stone. Internal & external use Agglomerates, engineered stone		
Benefits:	Where to apply:						
Oil / Water repellent Breathable, low odour Deeper penetration Non yellowing- UV resistant Long lasting protection	Polished textured, honed marbles, granites, natural stone. Internal & external use Agglomerates, engineered stone						
How to use :	<p>Always test first before proceeding with complete product application so to determine product compatibility and final result on material. Protect and cover all surroundings and metallic fixings using PVC sheeting and tape. Wear suitable PPE equipment during product use (gloves, eye protection and clothing). Product is ready for use. Do not apply where temperatures are below 10°C</p> <p>Always apply to clean, dry and dust free surfaces.</p> <p>Polished surfaces:</p> <ol style="list-style-type: none">1. Apply one coat ZEUS uniformly by low pressure spray, cotton cloth or soft bristle brush. Allow contact time of 5/10 minutes so to allow a complete penetration into material before removing excess product using a clean cotton cloth.2. After approximately 1 hour, remove eventual residues using a white felt pad.3. Allow a complete curing time of surface for 72 hours for complete surface protection. <p>Honed and textured surfaces:</p> <ol style="list-style-type: none">1. Apply one coat ZEUS uniformly by low pressure spray or brush.2. Allow contact time of 5/10 minutes so to allow a complete penetration into material. On very absorbent surfaces, proceed to apply a second coat before removing excess product using a clean cotton cloth or lambswool applicator.3. Allow a complete curing time of surface for 72 hours for complete surface protection.						
Maintenance:	<p>Surfaces treated with ZEUS are compatible with pH neutral detergents. Please refer to the below products for cleaning of treated surface. (please refer to product TDS for full product use and instructions:</p> <table><tr><td>Floors:</td><td>Daily: DETERCLEANER Sanitizer: DETERSAN</td><td>Periodic: DETERMAC</td></tr><tr><td>Worktops and surfaces:</td><td>Daily : DETERSAN trigger</td><td>Periodic: QUARTZ CREAM</td></tr></table>	Floors:	Daily: DETERCLEANER Sanitizer: DETERSAN	Periodic: DETERMAC	Worktops and surfaces:	Daily : DETERSAN trigger	Periodic: QUARTZ CREAM
Floors:	Daily: DETERCLEANER Sanitizer: DETERSAN	Periodic: DETERMAC					
Worktops and surfaces:	Daily : DETERSAN trigger	Periodic: QUARTZ CREAM					
Safety and technical data:	<p>Before using this product, please read completely product label, TDS and SDS , available from your local dealer or contacting GCHEM. Keep package closed and stored in a cool place. Keep out of the reach of children. Always supply adequate ventilation when using product indoors and do not eat or drink during product use. Shelf life: 1-2 years.</p> <table><tr><td>Appearance: Limpid</td><td>Odour: Mild Solvent</td><td>Specific Density (20°C) : 0,820 gr/cm³</td></tr><tr><td>Colour: Transparent</td><td>pH: n/a</td><td>Flashpoint : ≥62°C</td></tr></table>	Appearance: Limpid	Odour: Mild Solvent	Specific Density (20°C) : 0,820 gr/cm³	Colour: Transparent	pH: n/a	Flashpoint : ≥62°C
Appearance: Limpid	Odour: Mild Solvent	Specific Density (20°C) : 0,820 gr/cm³					
Colour: Transparent	pH: n/a	Flashpoint : ≥62°C					
Coverage:	Based on type of material and porosity, 1lt of product will cover from 5 m2 (highly absorbent) up to 30 m2 (dense materials)						
Packaging : *ADR regulated	1l. (box 10 pcs) 5l. (box 2 pcs) 10l. on request * 25l. on request. *						

Our technical advice, whether verbal or in writing is given in good faith without warranty and should not be considered binding towards third parties. We highly suggest that product is used always under the best professional working conditions possible. Product use and application is under the sole responsibility of the user and beyond our control. We guarantee product quality as of our production standards and supplied terms and conditions. Should, in spite of this, liability be established for any damage, it will be limited to the value of the goods delivered by us and used by you.